Truck Locks and Pallet Feet

4040, TLCH and TLCM Series

Foot operated Truck locks for immobilising mobile equipment. A choice of Top Plate or Side Plate fitting units are available. It is important that locks are fitted correctly according to the specification to enable optimum performance.











Fitting Type	Suits Wheel Sizes (mm)	Operating Height (mm)	Retracted Height (mm)	Plate / Bolt Hole Dimensions		Suits Bolt	Finish	Unit	Catalogue
				Plate (mm)	Bolt Ctrs (mm)	Dia. (mm)	rinish	Weight (kg)	Reference
4040 Se	ries Desi	gned to allow ca	stored equipme	nt to be immobili	sed in most locations	by a simpl	e foot pedda	l operation.	
Top Plate	100	143	119	137 X 94	92 × 67	10	Bronze	4	4040-010
Top Plate	100	150	125	120 X 120	85/100 × 85/100	10	Green	2	4040-020
Top Plate	150	210	170	120 X 120	85/100 × 85/100	10	Green	2	4040-020
TLCH S					is ESSENTIAL that the correct operation as			unted with the	top face
Top Plate		208	163.5	152 X 114	127 X 63.5	12	Black	5.6	TLC

TLCM Series Designed to be bolted onto the side or end of the truck. Fixing holes can be drilled to suit by the user. Four 10mm clearance fitting holes aresuggested, the top pair being 353mm and the lower pair not less than 226mm above the ground surface. When the locks are correctly fitted the foot pad must be 33mm from the floor with the linkage in the raised position. These locks are available in handed pairs. The Catalogue reference suffix R indicates the unit with the lever on the right.

Side Plate	-	381	346	165 X 114	Drill to suit	10	Bright Zinc	3	TLCMR
Side Plate	-	381	346	165 X 114	Drill to suit	10	Bright Zinc	3	TLCML


Pallet Feet

A range of Pallet feet and Nesting Plugs designed for fitting to Pallet legs of box or angle type.









1	1		
:		0	
:	1		1
1			/
	4	C	

Туре	Dimensions (mm)			Pall	et	SWG	Catalogue
	Α	В	С	Leg Type	Size (mm)	344.0	Reference
Pallet Foot	127 X 127	54	56	Box / Angle	50	13	KPFIA
Pallet Foot	165 X 165	54	76	Box / Angle	60 / 70	10	KPF2
Nesting Plug	53 X 53	38	032	Вох	40		KPF5